



F4, Perfluoropolyether, 0.5 l



F4, Perfluoropolyether, 0.5 l

- High- quality perfluoropolyether operating fluid for pumping down oxygen, ozone, halogens, organic and inorganic solvents, HCL, BF₃, HF, PO₃ and fluorine
- Used for high operating temperatures up to max. 120 °C
- For pumps with a pumping speed < 20 m³/h
- Extremely low vapor pressure, achievable ultimate pressure < 1 · 10⁻³ hPa

Technical Data

	F4, Perfluoropolyether, 0.5 l
Operating fluid attributes	For operation of the pump in 50 and 60 Hz mains Pumping of highly corrosive gases Pumping of gases with >21 % oxygen content Oxidation-resistant Resistant against acids and organic vapors Plasma etching compatible
Achievable ultimate pressure	<1 · 10 ⁻³ hPa <7.5 · 10 ⁻⁴ Torr <1 · 10 ⁻³ mbar

Order number

	F4, Perfluoropolyether, 0.5 l
F4, Perfluoropolyether, 0.5 l	PK 005 886 -T



Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum GmbH
Germany
T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 11/1/2024

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

