



# Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with splinter shield



Illustration only

**Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with splinter shield, hexagon bolts**

- For turbopump with HV-flange DN 63 ISO-K
- Suitable only for HiPace 30 to HiPace 80 and SplitFlow 50
- Collar flange DN 63 with retaining ring
- Centering ring with multi-functional coating for anti-twist protection
- Splinter shield: to safeguard against foreign objects, mesh width 0.8 mm, molecular conductance for N<sub>2</sub> 194 l/s
- 4 hexagon bolts M8 x 30 coated, with flange and washers
- Note: Required for secure mounting of the turbopump

Technical Data	Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with splinter shield, hexagon bolts
Mesh	0.8 mm
Molecular conductance for N <sub>2</sub>	194 l/s
Connection flange	DN 63 ISO-K

  

Order number	Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with splinter shield, hexagon bolts
Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with splinter shield, hexagon bolts	PM 016 931 -T



Errors and/or changes excepted. - 2/20/2025

**Are you looking for an optimum vacuum solution?**

**Talk to us:**

**Pfeiffer Vacuum GmbH**

**Germany**

**T +49 6441 802-0**

**Or scan the barcode, to visit our web page:**



<https://webportal.pfeiffer-vacuum.com/global/en/contact>

**Follow Us On Social Media**

**#pfeiffervacuum**



[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

**PFEIFFER** 