







Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, hexagon bolts



Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen

PFEIFFER >



Illustration only

Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, hexagon bolts

- For turbopump with HV-flange DN 63 ISO-K
- Suitable only for HiPace 30 to HiPace 80 and SplitFlow 50
- Collar flange DN 63 with retaining ring
- Centering ring with multi-functional coating for anti-twist protection
- Protective screen: to safeguard against foreign objects, mesh width 4 mm, molecular conductance for N₂ 303 l/s
- 4 hexagon bolts M8 x 30 coated, with flange and washers
- Note: Required for secure mounting of the turbopump

Technical Data	Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, hexagon bolts
Mesh	4 mm
Molecular conductance for N ₂	303 l/s
Connection flange	DN 63 ISO-K

Order number	Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, hexagon bolts
Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, hexagon bolts	РМ 016 932 -Т







Are you looking for an optimum vacuum solution? Talk to us: Pfeiffer Vacuum GmbH Germany T +49 6441 802-0 Or scan the barcode, to visit our web page:



https://webportal.pfeiffer-vacuum.com/global/en/contact

Follow Us On Social Media #pfeiffervacuum



www.pfeiffer-vacuum.com

