











Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen

PFEIFFER



Illustration only

Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, stud screws

- For turbopump with HV-flange DN 63 ISO-K
- Suitable only for HiPace 30 to HiPace 80 and SplitFlow 50
- Collar flange DN 63 with retaining ring
- Centering ring with multi-functional coating for anti-twist protection
- Protective screen: to safeguard against foreign objects, mesh width 4 mm, molecular conductance for N₂ 303 l/s
- 4 stud screws M8 x 30 coated and nuts with flange
- Note: Required for secure mounting of the turbopump

Technical Data	Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, stud screws
Mesh	4 mm
Molecular conductance for N ₂	303 l/s
Connection flange	DN 100 ISO-F

Order number	Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, stud screws
Mounting kit for DN 63 ISO-K to ISO-F, with collar flange, coated centering ring with protection screen, stud screws	PM 016 937 -T







Are you looking for an optimum vacuum solution?

Talk to us: Pfeiffer Vacuum GmbH Germany T +49 6441 802-0

Or scan the barcode, to visit our web page:



https://webportal.pfeiffer-vacuum.com/global/en/contact

Follow Us On Social Media #pfeiffervacuum













