



P3, mineral oil, 20 l



P3, mineral oil, 20 l

- High- quality mineral oil for standard applications to pump down air, inert gases and noble gases
- Used for high operating temperatures up to max. 95 °C
- Extremely low vapor pressure, achievable ultimate pressure $< 1 \cdot 10^{-3}$ hPa

Technical Data	P3, mineral oil, 20 l
Operating fluid attributes	For operation of the pump in 50 and 60 Hz mains Conveyance of non-corrosive gases Oxidation-resistant
Achievable ultimate pressure	$< 1 \cdot 10^{-3}$ hPa
Achievable ultimate pressure	$< 1 \cdot 10^{-3}$ hPa $< 7.5 \cdot 10^{-4}$ Torr $< 1 \cdot 10^{-3}$ mbar
Operating fluid amount	20 l

Order number	P3, mineral oil, 20 l
P3, mineral oil, 20 l	PK 001 108 -T



Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum GmbH
Germany
T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 11/1/2024

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

