



# Saturation indicator, optical/electrically for OME 40 M



Similar Image

## Saturation indicator, optical/electrically for OME 40 M

- Monitors the admissible back pressure at OME caused by dirty filter elements
- In addition to the optical display recognizable by a switching contact
- Mounted at the OME 40 M

Technical Data	Saturation indicator, optical/electrically for OME 40 M
Contact	Closing contact, normally open
Protection degree	IP55
Switching current V AC	0.7 A
Switching current V DC	1 A
Switching voltage	200 V DC
Switch-point	700 hPa

  

Order number	
Saturation Indicator	<b>P 0991 684</b>

## **VACUUM SOLUTIONS FROM A SINGLE SOURCE**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

## **COMPLETE RANGE OF PRODUCTS**

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

## **COMPETENCE IN THEORY AND PRACTICE**

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a  
perfect vacuum solution?  
Please contact us:

**Pfeiffer Vacuum GmbH**  
Headquarters · Germany  
T +49 6441 802-0  
info@pfeiffer-vacuum.de

[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

All data subject to change without prior notice.

**PFEIFFER**  **VACUUM**