



PFEIFFER 




Illustration only

ZFO 16, zeolite trap

- Prevents operating fluid backflow on the intake side

Technical Data	ZFO 16, zeolite trap
For pumping speed up to	5 m ³ /h
Conductance at $1 \cdot 10^{-2}$	0.3 l/s
Mounting orientation	0° (HV flange top) – 90°
For pumping speed up to	5 m ³ /h 2.943 cfm 83.335 l/min
Conductance at 1 hPa	0.7 l/s
Conductance at $1 \cdot 10^{-2}$	0.3 l/s
Conductance at 100 hPa	31 l/s
Weight	1.5 kg 3.31 lb
Heating rod	No
Weight with contents	1.5 kg
Filling quantity	0.5 l
Conductance at 1 hPa	0.7 l/s
Conductance at 100 hPa	31 l/s
Connection flange	DN 16 ISO-KF / DN 16 ISO-KF
Connection flange (in)	DN 16 ISO-KF
Connection flange (out)	DN 16 ISO-KF

Order number	ZFO 16, zeolite trap
ZFO 16, zeolite trap	PK Z70 003



Errors and/or changes excepted. - 2/21/2025

Are you looking for an optimum vacuum solution?

Talk to us:

Pfeiffer Vacuum GmbH

Germany

T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>

Follow Us On Social Media

#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 