



# D2, synthetic diester based oil, 1 l

## D2, synthetic diester based oil, 1 l

- High-quality synthetic diester based oil for standard applications to pump down air, inert, noble and slightly corrosive gases
- Used for high operating temperatures up to max. 120 °C
- Extremely low vapor pressure, achievable ultimate pressure <math>5 \cdot 10^{-2}</math> hPa

Technical Data	D2, synthetic diester based oil, 1 l
Achievable final pressure	$\leq 5 \cdot 10^{-2}$ hPa   $\leq 3.75 \cdot 10^{-2}$ Torr   $\leq 5 \cdot 10^{-2}$ mbar
Operating fluid amount	1 l
Operating fluid attributes	Oxidation-resistant Polymerization-resistant Pumping of NH <sub>3</sub> , R124a, refrigerating liquids For operation of the pump in 50 and 60 Hz mains Pumping of slightly corrosive gases High thermal stability
Order number	
D2	PK 005 875 AT

## **VACUUM SOLUTIONS FROM A SINGLE SOURCE**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

## **COMPLETE RANGE OF PRODUCTS**

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

## **COMPETENCE IN THEORY AND PRACTICE**

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a  
perfect vacuum solution?  
Please contact us:

**Pfeiffer Vacuum GmbH**  
Headquarters · Germany  
T +49 6441 802-0  
info@pfeiffer-vacuum.de

[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

All data subject to change without prior notice.

**PFEIFFER**  **VACUUM**