Material Safety Data Sheet



SW 60 Vacuum Pump Oil

1. Product and company identification

Product name	: SW 60 Vacuum Pump Oil
Material uses	: Analytical chemistry. Lubricant. 6040-1361 Oil, Vacuum Pump, 1L bottle 8829954400 Oil, Vacuum Pump, MS40 RVP, 1L
Supplier/Manufacturer	: Agilent Technologies, Inc. Logistics Center - Americas 500 Ships Landing Way New Castle, Delaware 19720 800-227-9770
Part No.	: 6040-1361, 8829954400
Validation date	: 05/07/2013
In case of emergency	: Chemtrec: 1-800-424-9300

2. Hazards identification **Physical state** : Liquid. [Viscous liquid.] Odor : Petroleum oil [Slight] This material is considered hazardous by the OSHA Hazard Communication Standard (29 **OSHA/HCS** status CFR 1910.1200). **Emergency overview** : WARNING! Signal word : CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS Hazard statements MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER. : Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Precautions Do not get on skin or clothing. Avoid contact with eyes. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. : Eye contact. Inhalation. Ingestion. **Routes of entry** Potential acute health effects Inhalation : Irritating to respiratory system. Ingestion : No known significant effects or critical hazards. : Irritating to skin. Defatting to the skin. Skin : Irritating to eyes. Eyes Potential chronic health effects Chronic effects : Contains material that may cause target organ damage, based on animal data. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Contains material which may cause cancer. Risk of cancer depends on duration and Carcinogenicity level of exposure. Mutagenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Teratogenicity **Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards. Target organs : Contains material which may cause damage to the following organs: upper respiratory tract, skin, eyes.

Over-exposure signs/symptoms

Date of issue :	05/07/2013	1/7

SW 60 Vacuum Pump Oil

2 Hazards identification

Z. Hazaros id	entification
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation redness dryness cracking
Eyes	: Adverse symptoms may include the following: pain or irritation watering redness
Medical conditions aggravated by over- exposure	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

-

3. **Composition/information on ingredients**

Name	CAS number	%
Mixture of severely hydrotreated and hydrocracked base oil (petroleum)		60 - 100

The base oil may be a mixture of the following CAS#: 8042-47-5, 64742-46-7, 64742-52-5, 64742-54-7, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1, 178603-64-0, 178603-65-1, 178603-66-2, 445411-73-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures		
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.	
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.	
Inhalation	: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.	
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	
Notes to physician	 No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	

5. Fire-fighting measures

- J J		
Flammability of the product	fire or if heated, a pressure increase will occur and the container r	nay burst.
Extinguishing media		
Suitable	an extinguishing agent suitable for the surrounding fire.	
Not suitable	e known.	
Special exposure hazards	ction shall be taken involving any personal risk or without suitable	training.
Hazardous thermal decomposition products	omposition products may include the following materials: on dioxide on monoxide	
Special protective equipment for fire-fighters	fighters should wear appropriate protective equipment and self-co aratus (SCBA) with a full face-piece operated in positive pressure	
Special remarks on fire hazards	s acrid smoke and irritating fumes when heated to decomposition.	
6 Accidental re	- maasuras	

6. Accidental release measures

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient	Exposure limits
Mixture of severely hydrotreated and hydrocracked base oil (petroleum)	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist

8. Exposure controls/personal protection

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Engineering measures	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eyes	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Other protection	: Not available.

9. Physical and chemical properties

•	• •
Physical state	: Liquid. [Viscous liquid.]
Flash point	: Open cup: >=220°C (>=428°F) [Cleveland.]
Auto-ignition temperature	: Not available.
Flammable limits	: Not available.
Color	: Colorless to light yellow.
Odor	: Petroleum oil [Slight]
рН	: Not available.
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Specific gravity	: 0.861 to 0.8682
Vapor pressure	: Not available.
Vapor density	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.

Date of issue :	05/07/2013			
-----------------	------------	--	--	--

SW 60 Vacuum Pump Oil

9. Physical and chemical properties

Viscosity	: 15: 38.1 cSt @ 40°C (104°F), 6.2 cSt @ 100°C (212°F), VI=108; 19: 55 cSt @ 40°C (104°F), 7.6 cSt @ 100°C (212°F), VI=100; 20: 103.1 cSt @ 40°C (104°F), 11.4 cSt @ 100°C (212°F), VI=97
Solubility	: Insoluble in the following materials: cold water and hot water.
Physical/chemical properties comments	: Pour point = 15: -18°C (0°F); 19: -15°C (5°F); 20: -12°C (10°F)
10. Stability ar	nd reactivity
Chemical stability	: The product is stable.
Conditions to avoid	: No specific data.

Conditions to avoid	
Materials to avoid	: Reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Mixture of severely hydrotreated and hydrocracked base oil (petroleum)	LC50 Inhalation Vapor	Rat	>2500 mg/m ³	4 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	>2000 mg/kg >5000 mg/kg	-

Irritation/Corrosion

Conclusion/Summary : Not available.

<u>Sensitizer</u>

Conclusion/Summary : Not available.

Chronic toxicity / Carcinogenicity / Mutagenicity / Teratogenicity / Reproductive toxicity Not available.

12. Ecological information

Ecotoxicity

- : May cause long-term adverse effects in the aquatic environment.
- Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SW 60 Vacuum Pump Oil

13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information				
DOT / IMDG / IATA /	: Not regulated.			
15. Regulatory information				
HCS Classification	: Irritating material Carcinogen Target organ effects			
U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined			
	United States inventory (TSCA 8b): Not determined.			
	SARA 302/304: No products were found. SARA 311/312 Hazards identification: Immediate (acute) health hazard, Delayed (chronic) health hazard			
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	: Not listed			
Clean Air Act Section 602 Class I Substances	: Not listed			
Clean Air Act Section 602 Class II Substances	: Not listed			
DEA List I Chemicals (Precursor Chemicals)	: Not listed			
DEA List II Chemicals (Essential Chemicals)	: Not listed			
State regulations				
Massachusetts	: None of the components are listed.			
New York	: None of the components are listed.			
New Jersey	: None of the components are listed.			
Pennsylvania	: None of the components are listed.			
<u>California Prop. 65</u>				
No products were found.				
16. Other information				

Label requirements	: CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER.	
Date of issue	: 05/07/2013	
Date of previous issue	: 05/01/2012.	
Version	: 3	
Indicates information that has changed from previously issued version.		

16. Other information

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.