<mark>능</mark> Diaphragm Type Dry Vacuum Pumps

DT

DAU-20 DTU-20

Features

- · High vacuum type diaphragm pump.
- · Low vibration.
- · High corrosion resistant. (DTU-20)

Applications

- Backing pump for TMP.
- Analytical equipment.
- · Biochemical analysis.
- · Gas charging.
- · Vacuum drying systems.
- Evaporators etc.





Specifications

Model		DAI	J-20	DTU-20			
	Unit	50Hz	60Hz	50Hz	60Hz		
Actual pumping speed	L/min	20	23	20	23		
Ultimate pressure	Pa	200		200			
Motor		Single phase, 100V, 8	Single phase, 100V, 80W, 4P, Capacitor run		Single phase, 100V, 80W, 4P, Capacitor run		
Full load current	Α	1.46		1.46			
Weight	kg	7.5		7.5			
Inlet, outlet pipe diameter	mm	O.D. dia.10 × I.[O.D. dia.10 × I.D. dia.6 (Rc 1/8)		O.D. dia.10 × I.D. dia.6 (Rc 1/8)		
Ambient temperature	°C	5 – 40		5 – 40			
Overall dimensions	mm	161(W) × 327(L) × 217(H)		161(W) × 327(L) × 217(H)			

Corresponding voltage and Certificate

Model	Voltage	Applicable Volt	CE Marked	TUV Marked	cTUVus Marked
DAU-20	Single phase, 100V	Standard	•	•	•
	Single phase, 115V	•	•	•	•
	Single phase, 200V	•	•	•	•
	Single phase, 220V	•	•	•	•
	Single phase, 230V	•	•	•	•
DTU-20	Single phase, 100V	Standard	•	•	•
	Single phase, 115V	•	•	•	•
	Single phase, 200V	•	•	•	•
	Single phase, 220V	•	•	•	•
	Single phase, 230V	•	•	•	•

Pumping speed curves

